






Model		Frequency	Load	Package	Stability @ 25C	Operating Temperature	Page
	BFC1x5	32.768kHz	8.0pF	1x5mm Can	20ppm	-10 C° to +60 C°	C3
	BFC2x6		12.5pF	2x6mm Can			
	BFC3x8			3x8mm Can			
	B306	32.768kHz	6-32pF/ Series	SMD	20ppm	-40C° to +85C°	C4
	B506	3.579545 to 90.0MHz	10pf-32pF/Series	SMD	50ppm	-40C° to +85C°	C5
	BFC32	12.0 to 55.0MHz	10pf-32pF/Series	3.2x2.5x0.7mm	±50ppm, ±30ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -40C° to +85C°	C6
	BFC42	13.0 to 32.0MHz	10pf-32pF/Series	4.0x2.5x0.8mm	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C7
	BFC53	8.0 to 250MHz	10pf-32pF/Series	5.0x3.2x1.0mm	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C8
	BFC64	12.0 to 150.0MHz	10pf-32pF/Series	6x3.5x1.1mm	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C9
	BFC64B	12.0 to 150.0MHz	10pf-32pF/Series	6x3.5x1.1mm	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C10
	BCC09	3.579545 to 40.0MHz	10pf-32pF/Series	3x9mm Can	±50ppm, ±30ppm ±20ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C11
	BCC10	4.0 to 70.0MHz		3x10mm can			
	BFCxxxx1	1.8432 to 200.0MHz	10pf-32pF/Series	HC-49U	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C12
	BFCxxxx2			HC-49T			
	BFCxxxx4	3.5 to 70.0MHz	10pf-32pF/Series	HC-49S	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C13
	BFCxxxx4S			HC-49SS			

Model		Frequency	Load	Package	Stability @ 25°C	Operating Temperature	Page
	BFCxxxx5B	3.5 to 70.0MHz	10-32pF/ Series	4mm/2lead	±100ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C14
	BFCxxxx5C			3.0mm/2lead	±50ppm		
	BFCxxxx5D			5.6mm/4leads	±30ppm ±20ppm		
	BFCxxxx5E			5.6mm/4leads	±10ppm		
	BFCxxxxU1	3.6864 to 225.0MHz	10-32pF/ Series	UM-1	±100ppm ±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C15
	BFCxxxxU5	10.0 to 225.0MHz	10-32pF/ Series	UM-5	±100ppm ±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C16
	BFC75	8.0 to 150.0MHz	10-32pF/ SERIES	7x5x1.3mm	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C17
	BFC75L	4.0 to 14.0MHz	10-32pF/ SERIES	7x5x1.3mm	±50ppm ±30ppm ±20ppm ±15ppm ±10ppm	0 C° to +70 C° -10 C° to +70 C° -20 C° to +70 C° -40C° to +85C°	C18
Standard Frequencies							C1A