

	<u>Description</u>	<u>Frequency Range</u>	<u>Package</u>
	<u>BFT16xxCS SERIES Clipped Sinewave Output FR-4 Package, TCXO</u>	8.0 to 40.0MHz	FR-4
	<u>BFT16xxT Series HCMOS SMD FR-4 PACKAGE, TCXO</u>	1.0 to 160MHz	FR-4
	<u>BT1653T Series HCMOS/TTL Ceramic SMD Ultra Miniature TCXO</u>	1.0 to 200.0 MHz	5.0x3.2x2.2mm
	<u>BT1657CS Series Clipped Sinewave SMD Package, TCXO</u>	9.6 to 40.0 MHz	5.0x7.0x2.5mm
	<u>BT1657T Series HCMOS/TTL Output SMD Package TCXO</u>	1.0 to 156.0 MHz	5.0x7.0x2.5mm
	<u>BT16xxCS Series HERMETIC SEAL DIL-14 Package , Clipped Sinewave, TCXO</u>	8 to 35.0MHz	DIL-14
	<u>BT16xxS Series HERMETIC SEAL DIL-14 Package Sinewave TCXO</u>	8 to 40.0MHz	DIL-14
	<u>BT16xxT Series HCMOS/TTL, HERMETIC SEALED DIL-14 TCXO</u>	1.0 - 200MHz	DIL-14
	<u>BTA16xxCS Series CLIPPED SINEWAVE, DIL-14(w/ Trimmer Hole) TCXO</u>	8 to 35.0MHz	DIL-14(w Hole)
	<u>BTA16xxS Series SINEWAVE, DIL-14(w/ Trimmer Hole) pkg., TCXO</u>	8 to 35.0MHz	DIL-14(w Hole)
	<u>BTA16xxT Series HCMOS/ TTL, DIL-14(w/ Trimmer Hole) pkg., TCXO</u>	1.0 to 200.0MHz	DIL-8